
## LSZ CO.

Grounding and Lightning Protection.
Technical Data Sheet

Product Name	Tape Conductor		
Product Code	CTC/TTC		
Application	Grounding/Earthing And Lightning Protection		
Applicable Standards	IEC/BS EN 62561  BS 7430		

Туре	Dimension							
Copper Tape	Width Thickness	20mm	25mm	30mm	50mm	60mm		
	2mm	Roll	Roll	Roll	-	-		
	3mm	Roll	Roll	Roll	-	-		
	4mm	ı	ı	Branch	Branch	Branch		
	5mm	1	1	-	Branch	Branch		
	6mm	1	•	-	Branch	Branch		
	10mm	-	-	-	Branch	Branch		
Stainless Steel / H.D.G Steel	2mm	Branch	Branch	-	-	-		
	3mm	Branch	Branch	Branch	-	-		
	5mm	-	-	-	Branch	Branch		



- Copper Tape Conductors can be Tin plated. (Ord. Code TTC)
- Aluminum Tape Conductors can be manufactured acc. To Order.
- Rolled Tape Conductors are each 100kg.(e.g. one 25x3mm Roll equals to 150m length.)
- H.D.G Steel Tape conductors are coated according to ASTM A123
- Stainless Steel Tape Conductors are grade AISI 304/316.





## CAJHIZAC SYSCEM ZAMIN CO.

Tel: +98 21 77940716/77959032 Fax: +98 21 77953528 E-Mail: Info@tsamin.com

