



Product Name	Flexible Tape
Product Code	FXT
Application	Grounding/Earthing And Lightning Protection Flexible Electrical Bonding (Doors / Fences ...)



Product Information		
Material	Copper / Aluminum	
Coating	Tin Plated for Copper	
Lug Size	10 or 12 mm Ø	
Production Method	Strand Braiding	
Length Limitation	5 cm – 2000 cm	
Types		
Ord. Code	Length (Cm)	Tape
FCT20x3-20	20	20x3 mm Copper
TFCT20x3-20	20	20x3 mm Tinned Copper
FCT20x3-25	25	20x3 mm Copper
TFCT20x3-25	25	20x3 mm Tinned Copper
FCT25x3-20	20	25x3 mm Copper
TFCT25x3-20	20	25x3 mm Tinned Copper
FCT25x3-25	25	25x3 mm Copper
TFCT25x3-25	25	25x3 mm Tinned Copper
FCT30x3-20	20	30x3 mm Copper
TFCT30x3-20	20	30x3 mm Tinned Copper
FCT30x3-25	25	30x3 mm Copper
TFCT30x3-25	25	30x3 mm Tinned Copper
FAT20x3-20	20	20x3 mm Aluminum
FAT20x3-25	25	20x3 mm Aluminum
FAT25x3-20	20	25x3 mm Aluminum
FAT25x3-25	25	25x3 mm Aluminum
FAT30x3-20	20	30x3 mm Aluminum
FAT30x3-25	25	30x3 mm Aluminum
List Of Accessories:	-	

